



Semi-Auto Batch Foaming Machine



Foam/Sponge producing machine with pneumatic motion, which can be used in Rectangular, Cubic and Cylindrical Molds. The speed of the Mixer can be controlled electronically from control panel. The small Raw-Materials are put in to the Tank manually. Its products used in Bed, Furniture and all kind Sponge Producing Factories.



Specification:

Mixing Tank Capacity:	180L~250L	Oil Hydraulic System:	1 Set
Mixer Total Power:	11KW	Electric Float Top System:	1 Set(Electric)
Mixing Speed:	2800r~4200r/min	Air Filtering System:	1 Set
Save Formula Q.T.Y.:	100 Groups	Water Tower:	1 Set
Control System:	PLC Touch Screen Control System	Water Pump:	1 Set
PPG Tank:	3 Ton * 1 Set	Foaming Density Range:	8~50kg/Cubicmeter
POP Tank:	3 Ton * 1 Set	Outputs:	48 Blocks/per day/8hrs (230m ³ /day)
TDI Tank:	2 Ton * 1 Set	Match With One Square Mould:	L2100mm*W2100mm*H1300mm(To Be Requested)
MC Tank:	1 Ton * 1 Set	Match With One Cylinder Mould:	Dia 1800mm*H2200mm(To Be Requested)
Air Valves:	Euro Standard	Total Motor Power:	Approx 25KW
Auto Loading & Feeding Pumps for PPG,POP,TDI,MC:	4 Sets ("Shanghai" Brand Made in China)	Machine N.W.:	Approx 6Ton
Chiller(Both Cooling & Heating System):	1 Set * 7.5KW(Made in Taiwan)	Floor Space Required:	L10m*W10m*H6m